




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁷ : C10G 47/00, C01B 3/38		A1	(11) International Publication Number: WO 00/69989
			(43) International Publication Date: 23 November 2000 (23.11.00)
(21) International Application Number: PCT/EP00/04396 (22) International Filing Date: 9 May 2000 (09.05.00) (30) Priority Data: 99303736.5 13 May 1999 (13.05.99) EP (71) Applicant (for all designated States except US): SHELL INTERNATIONALE RESEARCH MAATSCHAPPIJ B.V. [NL/NL]; Carel van Bylandtlaan 30, NL-2596 HR The Hague (NL). (72) Inventors; and (75) Inventors/Applicants (for US only): GOSSELINK, Johan, Willem [NL/NL]; Badhuisweg 3, NL-1031 CM Amsterdam (NL). GROENEVELD, Michiel, Jan [NL/NL]; Badhuisweg 3, NL-1031 CM Amsterdam (NL). NOWAK, Andreas, Karl [DE/NL]; Badhuisweg 3, NL-1031 CM Amsterdam (NL). ROOVERS, Antonius, Adrianus, Maria [NL/NL]; Badhuisweg 3, NL-1031 CM Amsterdam (NL).		(81) Designated States: AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i> <i>Before the expiration of the time limit for amending the</i> <i>claims and to be republished in the event of the receipt of</i> <i>amendments.</i>	
(54) Title: HYDROCARBON HYDROCONVERSION PROCESS FOR THE PRODUCTION OF HYDROGEN, HYDROPROCESSED HYDROCARBONS AND ELECTRICITY			



(57) Abstract

Method for producing hydrogen, electricity and at least one hydroprocessed product from a hydrocarbonaceous feedstock comprising at least a fraction which has a boiling point range which is the same or higher than the boiling point range of the hydroprocessed product to be produced, which method comprises subjecting the hydrocarbonaceous feedstock to a treatment with hydrogen in the presence of a supported catalyst, which hydrogen has been produced at least partly from a fraction of the hydrotreated feedstock having a boiling point range different from the boiling point range of the fraction of the hydrocarbonaceous feedstock from which the hydroprocessed product will be produced, or from at least part of said hydroprocessed product, separating the hydroprocessed product from hydrotreated feedstock when hydroprocessed product is to be recovered and subjecting part or all of the remaining hydrotreated feedstock and the hydroprocessed product if it is not to be recovered to a treatment to produce hydrogen and subjecting part or all of the hydrogen not used for the treatment with hydrogen to a treatment to produce electricity, or subjecting part of the hydrotreated feedstock and the hydroprocessed product if it is not to be recovered to a treatment to produce electricity and the remainder to a treatment to produce hydrogen.